

# THE BIGGEST DEVELOPMENT IN LIFTING SINCE GRAVITY.

Introducing the fully electric eLift by EnKon.



## PRODUCT FEATURES:

|                     |                             |
|---------------------|-----------------------------|
| PRODUCT TYPE        | Electric Scissor Lift Table |
| ACTUATOR            | Electric motor drive        |
| CAPACITY            | Up to 3000 lbs              |
| RAISED HEIGHT       | Up to 47"                   |
| BEARINGS            | Lubricated for life         |
| PIVOTS              | Replaceable hub             |
| WHEEL TRACKS        | Hardened                    |
| MAINTENANCE STOPS   | 2 quantity                  |
| POWER               | 220 VAC 3-phase             |
| SAFETY              | Bellows skirting            |
| FLOOR MOUNT TABS    | 3/4" holes, 4 quantity      |
| LIMIT SWITCHES      | Upper / lower               |
| PENDANT PUSH BUTTON | Up / down / E-stop          |
| FOOT CONTROLLER     | Up / down                   |
| COUNTRY OF ORIGIN   | USA                         |

## THE INDUSTRY'S FIRST ELECTRIC VERTICAL ROBOT

ELTO is the first industrial scissor lift table of its kind, featuring a breakthrough, patented, fully electric low-profile gearmotor transmission to deliver unmatched lift performance over high duty cycles.

**ELTO**<sup>™</sup>  
eLIFT BY ENKON

## HIGHER THINKING

[www.herkules.us](http://www.herkules.us)  
[www.enkon.pro](http://www.enkon.pro)  
(800) 444-4351

L0166

# GO ELECTRIC AND ELEVATE YOUR OPERATIONS.

Over time, hydraulic lift mechanisms lose pressure and leak fluid. This can cause job site safety issues, diminishing precision, poor reliability and a limited lifespan. ELTO utilizes a patented, fully electric drive system that delivers unmatched precision, reliably holding positions over high duty cycles. It uses no hydraulic fluid and requires very little maintenance. Plus, ELTO features a low profile for improved throughput and wide-ranging applications.



| MODEL            | TRAVEL (IN) | CAPACITY (LBS) | LOWERED HEIGHT (IN) | TRAVEL (IN) | RAISED HEIGHT (IN) | PLATFORM SIZE |             | SHIP WEIGHT (LBS) |
|------------------|-------------|----------------|---------------------|-------------|--------------------|---------------|-------------|-------------------|
|                  |             |                |                     |             |                    | WIDTH (IN)    | LENGTH (IN) |                   |
| VRE03-05-36-2448 | 24          | 500            | 11.7                | 24          | 35.7               | Ø 44          | 49.5        | 1000              |
| VRE03-10-36-2448 | 24          | 1000           | 11.7                | 24          | 35.7               | Ø 44          | 49.5        | 1050              |
| VRE03-20-36-2448 | 24          | 2000           | 11.7                | 24          | 35.7               | Ø 44          | 49.5        | 1100              |
| VRE03-30-36-2448 | 24          | 3000           | 11.7                | 24          | 35.7               | Ø 44          | 49.5        | 1150              |



| MODEL            | TRAVEL (IN) | CAPACITY (LBS) | LOWERED HEIGHT (IN) | TRAVEL (IN) | RAISED HEIGHT (IN) | PLATFORM SIZE |             | SHIP WEIGHT (LBS) |
|------------------|-------------|----------------|---------------------|-------------|--------------------|---------------|-------------|-------------------|
|                  |             |                |                     |             |                    | WIDTH (IN)    | LENGTH (IN) |                   |
| VRE15-05-43-4061 | 36          | 500            | 7                   | 36          | 43                 | 39.5          | 61          | 1200              |
| VRE15-10-43-4061 | 36          | 1000           | 7                   | 36          | 43                 | 39.5          | 61          | 1250              |
| VRE15-20-43-4061 | 36          | 2000           | 7                   | 36          | 43                 | 39.5          | 61          | 1300              |
| VRE15-30-43-4061 | 36          | 3000           | 7                   | 36          | 43                 | 39.5          | 61          | 1350              |



| MODEL            | TRAVEL (IN) | CAPACITY (LBS) | LOWERED HEIGHT (IN) | TRAVEL (IN) | RAISED HEIGHT (IN) | PLATFORM SIZE |             | SHIP WEIGHT (LBS) |
|------------------|-------------|----------------|---------------------|-------------|--------------------|---------------|-------------|-------------------|
|                  |             |                |                     |             |                    | WIDTH (IN)    | LENGTH (IN) |                   |
| VRE06-05-47-2456 | 36          | 500            | 10.5                | 36          | 46.5               | 24            | 56          | 1000              |
| VRE06-10-47-2456 | 36          | 1000           | 10.5                | 36          | 46.5               | 24            | 56          | 1050              |
| VRE06-20-47-2456 | 36          | 2000           | 10.5                | 36          | 46.5               | 24            | 56          | 1100              |
| VRE06-30-47-2456 | 36          | 3000           | 10.5                | 36          | 46.5               | 24            | 56          | 1150              |



ELTO Standard Foot Controller



ELTO Standard Hand Pendant