

### Model LSA40

Section 23

Travel 25"



An incredibly stable 4 scissor pneumatic lift that excels in handling side loads, the LSA40 Air Scissor Lift Table is both compact and reliable. Similar to the LSA25, the LSA40 provides the same low profile of 4" and a smaller platform of 36" x 57". With up to 25" of travel, the LSA40 offers a final raised height of 29" and can lift up to 6,000 lbs.

Ideal for integration into Just-in-Time (JIT) applications, the LSA40 can be utilized as a single lift, or stacked to reach even greater heights with ease and confidence.

EnKon.pro™

### Standard Features

- **100% air operated** for low maintenance, ease of use, and work environment safety
- **Low profile** accommodates a wide range of worker heights and applications
- **Modular design** is easily customizable to application specifications
- **High-strength steel, welded construction** built to safety factors required by customer application and in compliance with ANSI MH29.1-1994
- **High capacity lifting** up to 57,000 lbs (25,855 kg)
- **Variable duty cycles** from low to high for cost flexibility to fit each application
- **Self-lubricating PTFE overlay** on bearings at all pivot points for high loads and long life
- **Captured wheel guides** to prevent top and bottom lift platforms from tipping
- **Stackable lift modules** for added lift travel
- **Patented direct one-to-one lift ratio** in which the air bag supplies all of the lifting power, resulting in less stress on the scissors and increased lift longevity
- **Virtually maintenance-free** for low-cost operation and minimal downtime
- **Safety pressure release** helps prevent the air bag from overinflating
- **Enamel-based acrylic paint** applied to all surfaces after being cleaned and primed
- **Clean and green technology** for a cleaner and safer work environment

### Options

- **Lockout valve and filter regulator** enhances performance of the air supply
- **Piloted internal valves with check valves** prevent undesired lift descent
- **Portability kits** allows lift system to be moved with ease
- **High speed capability** with a full cycle in under 10 seconds
- **Safety skirting** to protect from pinch points and debris

Continued ↓

## Model LSA40

Section 23


Travel 25"



### Nomenclature

Product Type: Lift Scissor Air  
Lift Style: 40  
Capacity: 60 = 6000 lbs  
Raised Height: 29"  
Platform Size: 36" width x 57" length

Model LSA 40-60-29-3657



EnKon.pro™

Travel in	Model	Capacity lbs	Lowered Height in	Travel in	Raised Height in	Platform Size <sup>5</sup>		Base Size <sup>5</sup> in x in	Ship Weight <sup>1</sup> lbs
						Width in	Length in		
25	LSA40-10-29-3657	1000	4	25	29	36 - xx	57 - xx	36 x 57	1060
25	LSA40-20-29-3657	2000	4	25	29	36 - xx	57 - xx	36 x 57	1060
25	LSA40-30-29-3657	3000	4	25	29	36 - xx	57 - xx	36 x 57	1060
25	LSA40-40-29-3657	4000	4	25	29	36 - xx	57 - xx	36 x 57	1060
25	LSA40-50-29-3657	5000	4	25	29	36 - xx	57 - xx	36 x 57	1060
25	LSA40-60-29-3657	6000	4	25	29	36 - xx	57 - xx	36 x 57	1060

Values rounded to the nearest 1", see drawing for actual dimensions.

### Notes

- 1 Ship weights are estimated and do not include oversize platforms or options
- 2 Maximum air bag pressure is 50 psi or 100 psi depending on air bag type
- 3 Recommended air line feed pressure is 70 psi to 100 psi
- 4 Air consumption is 5 cubic feet per minute (cfm) on average based on cycle rate  
See the EnKon Systems website for how to calculate cfm for your application  
URL: <http://enkon.pro/blog/calculating-cfm-and-scfm-for-pneumatic-scissor-lift-tables/>
- 5 Width and length dimensions reference the main structure of the lift system and do not include structures such as floor tabs, bolt heads, etc. See drawing for actual dimensions
- 6 Surface finishes are either powder coat or low-VOC quick-dry two-stage spray-on primer coat and hard enamel top coat
- 7 Lifts must be center loaded when at full capacity
- 8 Side and end load capacities are derated 2% per inch of increase top plate size from base size
- 9 Safety bellow skirting option must be purchased to meet ANSI and OSHA standards