

Options

Rotate Features

- Air brake
- Spring detents – 90°
- Spring detents – 180°
- Spring detents – 360°
- Brake on indicator
- High-grade turret bearing – 15"
- High-grade turret bearing – 20"
- High-grade turret bearing – customer to specify
- Standard-grade rotate bearings

Tilt Features

- Heavy duty continuous hinge
- 10° to 90° tilt angle
- Steel tracks for positive lateral control
- Hard stop limited travel

Skirting Features

- Bolt-on
- Velcro-on
- Vent holes
- One to four sides
- Split corner for ease of replacement
- Reinforcement wire
- Weighted at base
- Variable bellows width

Safety Skirting

- Safety bellows – vinyl, black & yellow
- Safety bellows – vinyl, custom colors
- Safety bellows – polypropylene, black
- Safety bellows – fire retardant
- Steel skirting panels
- Steel skirting interlocking expandable

Operator Positioner Features

- Hand railing – welded in place
- Hand railing – removable
- Hand railing – pivoting
- Steps – welded in place
- Steps – removable
- Steps – pivoting
- Pivoting ramps – welded in place
- Pivoting ramps – removable
- Toe kick – welded in place
- Toe kick – removable
- Gate – hinged frame
- Gate – chain latch

Top Platform Features

- Pre-tapped holes
- Pre-drilled holes
- Custom top plate
- Corner gussets
- Full face gussets

Coatings/Finishes

- Custom colors available – enamel
- Epoxy food-grade paint
- Stainless steel available

Miscellaneous Plumbing

- Custom hose lengths
- Hard plumbing
- Hose protection sleeves
- Inline check valves

Options

Structural Features

- Captured wheel track
- Floor anchor holes
- Floor bumper stop
- Floor mounting tabs
- Fully redundant safety locking system
- Hard stops limited travel
- High duty cycle package
- High speed available
- Lowered height adjustable riser
- Manual safety stop block
- Mechanical locking system – arms
- Mechanical locking system – ratchet
- Portability – caster system
- Portability – dolly system
- Portability – rail system
- Risers available
- Toe guard
- Variable capacities
- Vertical hose management – Catrac®

Additional Features

- High flow male & female quick couplers
- Limit switches
- Automation control box
- Self-leveling
- Indexing controls
- CPU control logic
- String encoders

Controls

- Hand
 - Pendant – push button up/down/e-stop
 - Pedestal – push button up/down/e-stop
- Foot
 - Pedal – up/down
- Power Unit
 - Motor: 3/4 to 20 Hp
 - Motor Voltage:
 - 120 VAC
 - 240 VAC
 - 480 VAC
 - 24 VDC
 - 48 VDC
 - Solenoid Voltage:
 - 24 VAC
 - 120 VAC
 - 24 VDC
 - 48 VDC
 - Internally mounted
 - Externally mounted
 - Pedestal mounted

Safety Features

- Velocity Fuse
- Adjustable pressure compensated flow control valve
- E-stop button (detented with twist return)
- Safety toe stop